



Resonant Acoustic® Mixing Liquid Incorporation

Background

Resodyn Acoustic Mixers has developed a novel mixer product line that uses low-frequency, high-intensity sound energy for mixing. The mixer technology, trademarked as ResonantAcoustic® Mixing, is applicable to a broad range of mixing classes that include liquid-gas, liquid-liquid, liquid-solid and powder-powder systems. Highlighted in this bulletin is: **Blending Corn Syrup with Food Coloring**. This demonstrates the common application of dispersing aqueous liquids in low viscosity liquid.

Polymer-Liquid Blending

Food Coloring was blended with corn syrup. The image on the left depicts the starting materials while the image on the right shows the results after mixing. The starting materials were 300g of corn syrup and 3.0g of food coloring. The mixing was performed at 20°C with the corn syrup exhibiting a viscosity of 2100cp.

The materials were blended using the LabRAM® mixer. After only five seconds of mixing, the two materials were thoroughly blended, with the liquid fully dispersed within the corn syrup.

The use of RAM™ technology is well suited for dispersion of liquids into polymers. Mixing in the end container allows for quick batch cycle and no clean up of the mixing equipment.



Starting Materials

After 5 Seconds Mixing

ResonantAcoustic® Mixer Benefits

- Easy cleaning
- Fast mixing times
- Can mix in the shipping container
- Breaks loose agglomerations
- Safe for hazardous materials
- Can combine processing steps such as coating and mixing



LABRAM



SUPPORT

(주)비에스서포트

경기도 수원시 장안구 서부로 2066

성균관대학교 산학협력센터 85308호

Tel (031) 299-6786 Mobile 010-2259-5341

Fax (031) 299-6787

info@bssupport.co.kr www.bssupport.co.kr

